

## For Commercial and Residential Applications

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

# PurePro™

## Flexible Braided Stainless Steel Water Supply Connectors for Washing Machines

**Sizes:** ¾" (20mm)

PurePro Flexible Braided Stainless Steel Water Supply Connectors for Washing Machines are used in residential and commercial applications, specifically for washing machine hook-ups. These connectors provide full flow capacity and protection from vibration and bursting under pressure surges caused by washing machine solenoid valves. Connectors consist of PVC tubing jacketed with braided stainless steel, and permanently attached brass, compression end fittings. Various end connections are available.

### Features

- Available in lengths: 48", 60", and 72" (900, 1500, or 1800mm)
- Tubing
  - PVC body
  - Braided stainless steel jacket
- Brass compression end fittings and barbs

### Standards

UPC Listed



### Pressure-Temperature

Maximum Working Pressure: 125psi (8.6 bar)

Maximum Temperature: 180°F (82°C)

### Materials

Tubing:

Body: PVC

Jacket: Stainless steel

Fittings: Brass



PRO298000

### Models:

Supplied with standard brass female hose bib fittings at each end of the flexible connector.

### Dimensions



PUREPRO PART NO.	SIZE	INDIVIDUAL WGT. (LBS.)
PRO298000	¾" x ¾" x 48"	0.5
PRO298001	¾" x ¾" x 60"	0.8
PRO298002	¾" x ¾" x 72"	1.1

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



PurePro, Amherst, NH 03031