

PUREPRO® THERMOSTATS



DP5 II Digital Programmable 5-2 Heating & Cooling Thermostat

Features:

- | Energy Star certified
- | Separate programs for weekdays and weekends
- | Preprogrammed – up to 4 programs per day
- | Separate programs for heating and cooling
- | Either system powered with battery backup or battery powered, (2) “AA” batteries included
- | Lighted display with large liquid crystal display
- | Separate weekday and weekend programming
- | Easily reprogrammed with programming dial
- | 5 minute air conditioning compressor delay
- | Temporary and constant temperature override
- | Total isolation between system power and thermostat
- | Decorative wall plate is available

Compatible With:

- | Most single stage 24V gas, oil, electric heating and air conditioning systems, including single stage heat pumps
- | 2 wire hydronic systems
- | Millivolt systems
- | Hydronic air handler systems

Specifications

Temperature Differential	+ or – 1° factory preset differential adjustable from 1/4°F to 21/4°F.
Temperature Control Range	45°F to 90°F (7°C to 32°C) 12/24 hour time capable.
Terminals	G, Y, W, RH, RC, Solid pin connectors allow usage with both 24V and millivolt equipment.
Program Settings	4 preset programs per day heating and cooling. All may be easily reprogrammed in 1° and 15 minute increments with programming dial.
Circuit Protection	Circuit protection is built-in, no isolation relays required

PurePro®

1 Bon Terrain Drive
Amherst, NH 03031

PurePro

®

PUREPRO® THERMOSTATS



D111 Digital Non-Programmable

Heating & Cooling Thermostat

Features:

- | Electronic accuracy
- | Can be mounted horizontally or vertically
- | Large, easy-to-read digital display
- | EL (electro luminescent) backlight
- | Temperature swing adjustment to as close as + or - 1/4° F/C
- | System or battery powered, 2 "AA" batteries included
- | Low battery indicator
- | 5 or 2 minute compressor delay
- | Temperature offset (user calibration)
- | Decorative wall plate is available

Compatible With:

- | Most 24V Gas, Oil, Electric Heating and Cooling Systems
- | 2 wire hydronic systems
- | Millivolt systems
- | Hydronic air handlers
- | Single stage heat pumps

Specifications

Electrical Ratings	1 1/2 AMPS at 24V A/C
Temperature Control Range	+ or - 1/2° F/C
Terminals	G, Y, W, RH, RC, Solid pin connectors allow usage with both 24V and millivolt equipment.



D110 Digital Non-Programmable

Heating Thermostat

Features:

- | Electronic Accuracy
- | Universal decorative wall plate is available
- | Vertical style
- | Large, easy-to-read display
- | Temperature swing adjustment
- | Universal replacement
- | Low battery indicator

Compatible With:

- | Most 24v Gas, Oil, Electric Heating and Air Conditioning Systems
- | 2 Wire Hydronic Systems
- | Millivolt Systems
- | Hydronic Air Handlers

Specifications

Electrical Ratings	1 1/2 AMPS at 24V A/C. System or Battery Powered 2 "AA" Batteries (included)
Temperature Control Range	45°F to 90°F (7° to 32°). Accuracy ± 1°F over a range of 50°F to 95°F.

PurePro®

1 Bon Terrain Drive
Amherst, NH 03031

PurePro

®